


Series 23-CS

2-Piece Carbon Steel Ball Valve



FEATURES

- AISI 1017 Carbon Steel Bodies and Tailpieces
- 3000 WOG Rating on All Sizes, 1/4" to 1"
- 150 PSIG Saturated Steam Rating
- All Models are NACE MR-01-75 Compliant
- 316 Stainless Steel Ball & Stem Standard
- "Live Loaded" Stem Packing Design
- "Tamperproof" Locking Handles Available in Carbon and Stainless Steel
- Competitively Priced
- PEEK Seats Available



3000 SERSSOR 1500 1200 900 600 300 500 100° 200° 300° 400° 450° TEMPERATURE °F

RATINGS

3000 PSIG @ 100F Water, Oil, Gas All Sizes ... 150 PSIG Saturated Steam

MATERIALS OF CONSTRUCTION

DESCRIPTION	STANDARD MATERIAL	OPTIONAL MATERIAL(S)
DESCRIPTION	STANDARD WATERIAL	OF HOWAL WATERIAL(S)
BODY	AISI Gr. 1017	
TAILPIECE	AISI Gr. 1017	
BALL	ASTM A276 Gr. 316SS	
STEM	ASTM A276 Gr. 316SS	
PACKING NUT	Carbon Steel-Plated	
SEATS (2)	HOSTAFLON	PEEK
PACKING	R-PTFE	
WASHER	ASTM A276 Gr. 304SS	
THRUST WASHER (2)	TFE	
BELLEVILLE WASHER (2)	Carbon Steel-HT	
HANDLE ASSY	Carbon Steel-Plated	304 Stainless Steel
HANDLE NUT	Carbon Steel-Plated	304 Stainless Steel
BODY SEAL	R-PTFE	
	TAILPIECE BALL STEM PACKING NUT SEATS (2) PACKING WASHER THRUST WASHER (2) BELLEVILLE WASHER (2) HANDLE ASSY HANDLE NUT	BODY AISI Gr. 1017 TAILPIECE AISI Gr. 1017 BALL ASTM A276 Gr. 316SS STEM ASTM A276 Gr. 316SS PACKING NUT Carbon Steel-Plated SEATS (2) HOSTAFLON PACKING R-PTFE WASHER ASTM A276 Gr. 304SS THRUST WASHER (2) TFE BELLEVILLE WASHER (2) Carbon Steel-HT HANDLE ASSY Carbon Steel-Plated HANDLE NUT Carbon Steel-Plated

DIMENSIONS, WEIGHTS, CV FACTORS & MAXIMUM OPERATING TORQUE

SIZE	Α	В	С	D	E	WEIGHT LBS.	Cv	MAX. TORQUE
1/4-3/8″	.40	1.0	2.0	1.7	4.2	.6	9	40 IN-LB
1/2"	.54	1.1	2.3	1.7	4.2	.75	16	75 IN-LB
3/4"	.68	1.4	2.8	2.1	5.9	1.6	27	120 IN-LB
1"	.88	1.6	3.2	2.3	5.9	2.4	42	150 IN-LB



SERIES 23-CS

NUMBERING SYSTEM ... HOW TO ORDER

23 R C S R R LH TT 100

PORT SIZE ENDS SERIES BODY MATERIAL BALL/STEM MAT'L SEAT MAT'L SEAL MAT'L HANDLE TYPE SIZE 23 = 2F = FULLC = CARBONS = 316R = R-PTFER = R-PTFE LH = CS LEVER TT = FNPT025 = 1/4"P = PEEKLL = CS LATCH038 = 3/8"**PIECE** (1/4"-1/2") STAINLESS MT = MxF NPTLOCK 050 = 1/2"3000 R = REDUCEDSH = STAINLESS 075 = 3/4" WOG (3/4"-1") **LEVER** 100 = 1" SL = STAINLESS LATCH LOCK

OTHER QUADRANT PRODUCTS	to solve your Fluid Control Problems:
	i to borre rour i fuiu continui i fobicino.

SERIES 20-NP	Forged Brass 400WOG Reduced Port Ball Valves
SERIES 20-BP & BS	Cast Bronze 600WOG Full & Reduced Port Ball Valves with Brass or 316SS Trim
SERIES 20-CC & CS	Carbon Steel Bar Stock 2000WOG Reduced Port Ball Valves with Carbon or 316SS Trim
SERIES 21	Stainless Steel 2-Piece 1000WOG Full Port Ball Valves
SERIES S1	Seal Welded Stainless Steel 1000WOG Full Port Ball Valves
SERIES S2	Seal Welded Stainless Steel 2000WOG Reduced Port Ball Valves
SERIES SB	Seal Welded Stainless Steel 2160WOG Reduced Port Ball Valves
SERIES S3	Seal Welded Stainless Steel 3600WOG Reduced Port and Full Port Ball Valves
SERIES S5	Seal Welded Stainless Steel 5000WOG Reduced and Full Port Ball Valves
SERIES S6	Seal Welded Stainless Steel 6000WOG Reduced Port and Full Port Ball Valves with
	FNPT, MxF NPT & Socket Weld Ends
SERIES M1	3-Piece 4-Bolt Maintenance Design Brass 600WOG Full Port Ball Valves with
	Plated Brass or 316SS Trim
<u>SERIES UU</u>	3-Piece Double Union High Pressure Full Port Ball Valves in Carbon and Stainless
	Steel Construction with FNPT or Socket Weld Ends
SERIES BFV-D	2"- 48" Ductile Iron Butterfly Valves with Ductile, Aluminum Bronze, or CF8M Discs
	and Buna-N, EPDM or Viton Seats- Lever, Gear Operators or Pneumatic/Electric
	Actuators
SERIES BFV-A	2" - 12" A-395 Ductile Iron Butterfly, Split Shaft, all Disc Materials and Buna-N or

Viton Seats, NACE Compliant, Lever, Gear Operators or Electric/Pneumatic Actuators